
Release Notes – Windows CE 7.0 - Fusion X_2.03.0.0.027R

[Introduction](#)

[Description](#)

[Device Compatibility](#)

[Installation Instructions](#)

[Part Number and Release Date](#)

Introduction

Fusion is a suite of software, which allows for WLAN connectivity, configuration, status reporting, and diagnostics. This is a release of Fusion X2.03 for all Windows CE 7.0 products.

Description

This is a release of Fusion X2.03 for Windows CE 7.0. This release corrects the following issues:

- SPR 34700 - UI is missing encryption selection options [fields are empty] on CE7 for Chinese localized image.

➤ **Note:**

- All the SPR fixes in X2.02 are included in X2.03 as well.
- X2.03 supports IEEE 802.11r (Fast BSS Transition) specification.
- TKIP encryption type for Fusion profiles has been removed from UI interface while creating the profile through Fusion Profiles dialog box to comply with WFA (Wi-Fi Alliance) guidelines.

Device Compatibility

This software release has been approved for use with the following Zebra devices.

Device	Operating System	Fusion Version
MC92, MC32, VC70, WT41N0	Windows CE 7.0	Any previous X1.00 or X2.00 or X2.01 or X2.02 or X2.03 version

➤ **Note:**

- If you cannot find your product on the list, please contact a Zebra representative.

Installation Instructions

NOTE: Prior to installation, ensure that you are currently running an approved version of the Operating System from the table above. Otherwise, visit <https://www.zebra.com/us/en/support-downloads>

Manual Installation:

1. Copy FUSION_X_2.03.0.0.027R_MPA3_CE70.CAB or FUSION_X_2.03.0.0.027R_MPA3_CE70_NO_REBOOT.CAB to \Application folder of the device.
2. Execute it by tapping on it.
3. Press OK on the File Dialog and follow on screen instructions to complete installation.
4. Solution will be installed and the device will warm boot automatically if the cab installed is FUSION_X_2.03.0.0.027R_MPA3_CE70.CAB.
5. If the cab installed is FUSION_X_2.03.0.0.027R_MPA3_CE70_NO_REBOOT.CAB, warm boot the device after installing the cab.

Airbeam /Automated Installation:

1. Create an Airbeam package that will install FUSION_X_2.03.0.0.027R_MPA3_CE70.CAB or FUSION_X_2.03.0.0.027R_MPA3_CE70_NO_REBOOT.CAB.
2. Use Airbeam client to install it.
3. If the Airbeam package installs the FUSION_X_2.03.0.0.027R_MPA3_CE70_NO_REBOOT.CAB, reboot of the device should be performed by the Airbeam package after installing the cab.

Version History

Fusion X2.03.0.0.021R, November 2017

Bugs Fixed:

- Corrections for KRACK vulnerabilities applied. Refer to the security bulletin for further details on KRACK vulnerability.
<https://www.zebra.com/us/en/support-downloads/lifeguard-security/lifeguard-krack.html>
- SPR 33055 - Fusion tries to associate to an AP with FT (802.11r) parameters even though the AP is not completely configured for FT

Part Number and Release Date

2_03_27R_MPA3_CE70

July 3, 2018