Release Notes – Windows CE 7.0 - Fusion X_2.03.0.0.018R

Introduction

Description

Device Compatibility

Installation Instructions

Part Number and Release Date

Introduction

Fusion is a suite of software, which allows for WLAN connectivity, configuration, status reporting, and diagnostics. This is a release of Fusion X2.03 for all Windows CE 7.0 products.

Description

This is a release of Fusion X2.03 for Windows CE 7.0. This release corrects the following issues:

- SPR 31072 Device fails to present proper FT capabilities to the Access Point which prevents fast roaming (802.11r) on the WLAN.
- SPR 31759 Secondary DNS server address which is added while creating a Fusion profile using FusionPublicAPI calls does not persist.
- SPR 30321 WLAN authentication fails when using PEAP/MSCHAPv2 with CA certificates.
- SPR 30843 If the SSID is hidden, Fusion does not report more than one AP in known APs page.
- SPR 30435 Device sometimes fails to roam to Avaya APs. Fix is taken from Android SPR.
- SPR 29002 Fusion probe for configured WLAN does not elicit probe response from hotspot.
- SPR 29343 Unable to connect when 802.11k is enabled in Cisco infrastructure.
- SPR 27276 UI is missing encryption selection options [fields are empty] on CE7 for Japanese localized image.

Note:

- All the SPR fixes in X2.02 are included in X2.03 as well.
- X2.03 supports IEEE 802.11r (Fast BSS Transition) specification.
- TKIP encryption type for Fusion profiles has been removed from UI interface while creating the profile through Fusion Profiles dialog box to comply with WFA (Wi-Fi Alliance) guidelines.
- Added support for ETSI RE-D compliance

Device Compatibility

This software release has been approved for use with the following Zebra devices.

Device	Operating System	Fusion Version
MC92, MC32, VC70, WT41N0	Windows CE 7.0	Any previous X1.00 or X2.00 or X2.01 or X2.02 or X2.03 version

Installation Instructions

NOTE: Prior to installation, ensure that you are currently running an approved version of the Operating System from the table above. Otherwise, visit https://www.zebra.com/us/en/support-downloads

Manual Installation:

- 1. Copy FUSION_X_2.03.0.0.018R_MPA3_CE70.CAB or FUSION_X_2.03.0.0.018R_MPA3_CE70_NO_REBOOT.CAB to \Application folder of the device.
- 2. Execute it by tapping on it.
- 3. Press OK on the File Dialog and follow on screen instructions to complete installation.
- 4. Solution will be installed and the device will warm boot automatically if the cab installed is FUSION X 2.03.0.0.018R MPA3 CE70.CAB.
- If the cab installed is FUSION_X_2.03.0.0.018R_MPA3_CE70_NO_REBOOT.CAB, warm boot the device after installing the cab.

Airbeam /Automated Installation:

- 1. Create an Airbeam package that will install FUSION_X_2.03.0.0.018R_MPA3_CE70.CAB or FUSION_X_2.03.0.0.018R_MPA3_CE70_NO_REBOOT.CAB..
- 2. Use Airbeam client to install it.
- 3. If the Airbeam package installs the FUSION_X_2.03.0.0.018R_MPA3_CE70_NO_REBOOT.CAB, reboot of the device should be performed by the airbeam package after installing the cab.

Part Number and Release Date

2_03_18R_MPA3_CE70